

PURITY™ FG SEAMER-E FLUID

Introduction

PURITY™ FG Seamer-E fluid is a high performance, advanced food grade lubricant specially designed for use in the food canning industry.

PURITY FG Seamer-E fluid is a mineral oil based, water emulsifying fluid that is formulated for use in high-speed continuous lubrication seaming units where contamination of the oil with water, food juices and sugar may occur. It is designed to lubricate the main turrets, bearings, chains and gears for smooth and effective equipment performance.

PURITY FG Seamer-E fluid provides viscosity control in the presence of water, and excellent load-carrying properties and corrosion inhibition to protect seamer components.

PURITY FG Seamer-E fluid meets the highest food industry safety standards and fits perfectly in HACCP (Hazard Analysis and Critical Control Point) and GMP (Good Manufacturing Practice) plans. All components comply with FDA regulation 21 CFR 178.3570 "Lubricants with incidental food contact".

PURITY FG Seamer-E fluid is registered by NSF as an H1 lubricant for use in food processing plants where incidental food contact may occur.

PURITY™ FG Seamer-E Fluid is suitable for use in Pneumatic Scale Angelus™ series such as 61/62H, 80/81L, 100/101L, 120/121L, 140S, 180S and 12M. Specific application and working environment should be evaluated by technical personnel.

Performance Benefits

- **Strong Load Carrying Characteristics**
 - Excellent load carrying properties promote effective seamer performance and equipment protection
- **Excellent Water Control**
 - Viscosity control
 - Emulsifying formulation
 - Corrosion inhibition
- **H1 registered by NSF for use in and around food processing areas**



Nonfood Compounds
Program Listed H1

Applications

PURITY FG Seamer-E Fluid may be used to lubricate the main turrets, bearings, gears and chains of high-speed seamer units that use recirculating lubrication and have a filtration system to help remove contaminants and water. PURITY FG Seamer-E fluid is also specially designed for systems using "once through" lubrication where the contamination of the lubricant with water, food juices, and sugar may occur.

What is the HT difference?

Petro-Canada Lubricants starts with the HT purity process to produce water-white, 99.9% pure base oils. The result is a range of lubricants, specialty fluids and greases that deliver maximum performance for our customers.



Typical Performance Data

PROPERTY	TEST METHOD	PURITY FG SEAMER-E FLUID
Appearance		Clear
Density, kg/L @ 15°C	D4052	0.872
Viscosity, cSt @ 40°C (SUS @ 100°F) cSt @ 100°C (SUS @ 210°F)	D445	140 (732) 14.7 (78)
Viscosity Index	D2270	104
Flash Point, COC, °C (°F)	D92	240 (464)
Pour Point, °C (°F)	D5950	-21 (-21)
Water separability, mL @ 82°C (180°F), minutes	D1401	0-37-43 (30)
Rust A	D665A	Pass
4-Ball Wear Scar diam., mm	D4172	0.4
4-Ball EP Weld Load, kgf	D2783	160
FZG Scuffing load capacity, Failure load stage	D5182 A/8.3/90	> 12

To order product or to learn more about how Petro-Canada Lubricants can help your business visit: lubricants.petro-canada.com or contact us at: lubecsr@petrocanadalsp.com



IM-8048E (2015.12)

™ Owned or used under license.

Beyond today's standards.™

