

INNOVATE™

Faster. Cooler. Cleaner.

INNOVATE™ PEYTO

Advanced Immersion Cooling Fluid

For high-performance computing applications

- Single-phase dielectric fluid designed for workloads that require exceptional heat transfer
- Formulated with our proprietary ultra-pure, Highly Refined Alkanes™ technology
- Best-in-class thermal management through optimized physical profile
- Designed for balanced materials compatibility performance across a wide range of material types
- Engineered for superior oxidative stability to ensure reliable and consistent performance in service

PROPERTY	UNITS	STANDARD	TYPICAL VALUE
Kinematic Viscosity @ 40°C	cSt	ASTM D445	3.58
Kinematic Viscosity @ 100°C	cSt	ASTM D445	1.37
Specific Heat Capacity @ 25°C	J/(kg-K)	ASTM E1269	2000
Thermal Conductivity @ 25°C	W/m-K	ASTM D7896	0.125
Figure Of Merit 1 @ 50°C	—	OCP	60.6
Figure Of Merit 2 @ 50°C	—	OCP	29.1
Density @ 15°C	kg/m ³	ASTM D4052	827.4
Pour Point	°C	ASTM D97	-66
Flash Point (Closed Cup)	°C	ASTM D93	128
Water Content	ppm	ASTM D1533	< 20
Color	—	ASTM D1500	< 0.5
Dielectric Strength	kV/mm	ASTM D1816	> 22
Dielectric Constant @ 25°C & 60 Hz	—	ASTM D924	< 2.2

LUB4422E (2024.10)

HF Sinclair™



sonneborn



HF SINCLAIR BRANDS